

Stannah vs Aritco vs Cibes: Home Lift Models Compared

By [DirectHome Team](#)

Updated 16 September 2026

9 min read

[Explore our home lifts service](#) ↗


Stannah, Aritco and Cibes overlap more than their brand images suggest: the Stannah Midilift PL2, Aritco HomeLift Access and Cibes A5000 are all screw-driven platform lifts. The practical differences include how many floors they can serve, the shape of the usable platform and the available controls. Aritco's Access range includes longer platforms and non-European control options; Cibes A5000 has closely specified shaft and floor-opening sizes; Stannah PL2 offers a comparable platform but its current Singapore supply needs confirmation. There is no supported reason to name one brand the smoothest or cheapest.

Need advice for your home?


[WhatsApp our team](#) ↗




Compare configurations on the same brief



Model A



Model B




Model C

Use the same household brief

Schematic • not to scale

Request a specified configuration from each provider using the same household brief. The drawing shown is a comparison aid, not a depiction of named products.

Three Comparable Platform Lifts



For a home-lift installation, the comparison should start with lifts that solve the same journey. Here that means an indoor vertical platform lift with roughly 1,100 mm of platform width, suitable for assessing wheelchair access. It does not mean the smallest standing-person lift from one brand against a large cabin from another. Wheelchair fit also depends on its length, the doorway and the space to approach it.


Manufacturer reference configurations, not quotations or approved building drawings. Stannah and Cibes higher-load options must be checked against the selected configuration. The Aritco platform is only 13 mm deeper in these examples.

Comparable model reference	Platform example: width × depth	Published load for this comparison	Maximum travel / stops
Stannah Midilift PL2	1,100 × 1,467 mm	400 kg; 500 kg option in the range	12 m / 5 stops
Aritco HomeLift Access, size 6	1,100 × 1,480 mm	410 kg in the 2026 datasheet	13 m / 6 floors
Cibes A5000, size 16	1,100 × 1,467 mm	400 kg; 500 kg option in the range	15 m / 6 stops

These dimensions and limits come from the [Stannah PL2 model page](#), [Aritco's 2026 Access datasheet](#) and [Cibes' technical specification](#). Maximum travel is the vertical distance between the lowest and highest stops, not the building's overall height. In an ordinary two- or three-stop proposal, all three published limits may be ample; a six-stop requirement excludes this PL2 specification.

Aritco HomeLift Access has a [public Singapore product listing](#). Stannah's Singapore distribution listing relates to stairlifts, and current local supply of PL2 has not been established here. Treat PL2 as a technical reference until a Singapore supply and support arrangement is confirmed. Cibes' global A5000 specification likewise does not, by itself, confirm local stock, delivery dates or the exact version offered.

Stannah: PL2 Platform or CLS Cabin?



The [Midilift PL2](#) uses an electric screw drive housed within its own structure, so it does not need a separate machine cabinet. The platform moves vertically within the enclosure, and the passenger keeps pressure on the travel control. Its published speed is 0.15 m/s, with a 50 mm pit or ramp option. Those basic characteristics overlap with Aritco Access and Cibes A5000; choosing Stannah does not automatically buy a faster or hydraulically driven lift.

The PL2's five-stop limit is a real distinction from the six-floor Aritco and six-stop Cibes specifications. For fewer floors, its value depends more on the entry arrangement and the installation offered. Stannah lists single, through, adjacent and three-sided entrances, which can help when landings face different directions. The actual doorway and approach space must still suit the wheelchair and any companion.


If the quotation instead says Midilift CLS, the comparison changes. The CLS is a hydraulic cabin platform lift with automatic sliding doors and automatic travel controls. Its standard published pit is 150 mm and its structure-supported headroom is 2,600 mm. That is a different drive and cabin arrangement, with a different building requirement, rather than an upgraded finish on the PL2. Its Singapore availability also needs confirmation.

Want an exact price for your home?

Ranges only go so far. WhatsApp us a photo of your space and we'll quote your actual job. No obligation.

[WhatsApp us](#) [Try the free cost estimator](#)

Aritco: Platform Length and Control Choices



The HomeLift Access size 6 provides a 1,100 × 1,480 mm carrier inside exterior dimensions of 1,500 × 1,600 mm. It is close in usable platform size to the Stannah and Cibes examples. The Access range also includes a longer 1,000 × 1,980 mm carrier and a 1,100 × 1,580 mm carrier, both rated at 500 kg in the 2026 datasheet. That extra length may be more useful than decorative features when a wheelchair and companion need to travel together.


Aritco's current datasheet also lists up to 0.25 m/s and one-touch operation for installations outside Europe, alongside the 0.15 m/s and hold-to-run versions. These are potential configuration differences worth investigating for Singapore, not an automatic entitlement to faster travel. The Singapore Access

[listing](#) describes 0.15 m/s and hold-to-run, so the faster or one-touch version must be expressly confirmed for the proposed local installation and approval.

For someone who struggles to keep a button pressed, that operating difference can matter more than a small change in platform dimensions. Try the control in the position the passenger will occupy, particularly if they use a wheelchair. The ability to enter the lift and the ability to operate it throughout the journey are separate parts of independent access.

Keep the Access separate from the smaller HomeLift Compact. The [Compact example](#) with a 580 × 805 mm carrier and an 840 × 880 mm exterior serves a different space requirement. It is not the wheelchair-sized competitor in the table. Distinguishing [carrier size from the surrounding lift and building opening](#) prevents a small external dimension from being mistaken for useful passenger space.

Cibes: Shaft Size Is Not the Floor Opening



For the Cibes A5000's 1,100 × 1,467 mm platform, the [technical drawing schedule](#) separates a 1,460 × 1,515 mm shaft from a 1,500 × 1,630 mm floor cut-out. The shaft is the lift's enclosure; the cut-out is the opening that the building needs. Quoting just the smaller shaft dimension would understate the required opening.

Against Aritco Access size 6, the Cibes shaft is 40 mm narrower and 85 mm shallower than Aritco's listed exterior. But the Cibes cut-out is larger than its own shaft. This is why Cibes cannot be declared the smallest installation simply by putting its shaft figure beside another model's building-opening


figure. The final floor openings, door swings and landing clearances decide how much room the house gives up.

The [A5000](#) shares the screw-and-nut drive and hold-to-run platform controls used in the basic comparison. It offers up to six stops and 15 m travel, with a 50 mm pit or ramp arrangement in the cited product specification. Its greater travel limit can matter in a taller house; it does not make a short ride faster. Its enclosure can be glazed, but glazing is a finish choice rather than evidence of a better ride.


A lift delivered with its own enclosure still needs support, floor openings, thresholds and a suitable electrical supply. The [site-preparation requirements](#) belong in the building plan. “Self-supporting” does not mean an existing slab or stairwell can accept the lift without assessment.

What the Differences Mean at Home


Keep three comparisons separate



Configuration



Building work



Aftercare

Match the scope before comparing totals

Schematic • not to scale

Equipment, building work and aftercare require separate comparisons. A brand preference does not establish the scope or cost of the local proposal.

The differences come from identified products and configurations. They are not whole-brand performance scores.

Decision	What the comparison actually establishes
Wheelchair and companion space	The three selected platforms are close in size. Aritco also documents longer 500 kg Access versions; Cibes offers other platform lengths too. Test the required occupants and entry route.


Decision	What the comparison actually establishes
Travel and controls	Standard comparison: 0.15 m/s and held control. Aritco additionally documents faster and one-touch versions outside Europe; local supply and acceptance are not established by that statement.
Number of floors	PL2: up to 5 stops. Access and A5000: up to 6. Check total travel as well as the number of stops.
Building opening	Aritco's exterior and Cibes' shaft measurements can be compared as enclosures. Neither is a substitute for the complete floor-opening drawing. PL2 opening dimensions remain configuration-specific.
Appearance	Glazing, floors and colours are configurable. None of these three brand names alone establishes traditional or modern finishes.
Price and aftercare in Singapore	No matched local quotations or comparative repair records establish a brand winner. Equipment, building work and support must be priced together.

At 0.15 m/s, a hypothetical 3 m of travel takes 20 seconds at constant speed; at 0.25 m/s it takes 12 seconds. These are distance divided by speed, not measured journey times. Starting, stopping, door movement and boarding add time. A household making occasional trips may care more about easy controls and a comfortable landing than this eight-second theoretical difference.

There is also no verified same-site ride or noise test here that makes Stannah smoother, Aritco quieter or Cibes more reliable. A demonstration can help the intended user judge comfort, but it should represent the quoted drive, controls and door arrangement. A hydraulic cabin demonstration cannot establish how a screw-driven platform version will feel.

Compare the installed equipment, openings and structural work, finishes, electrical work and approval-related scope in one upfront total. Then compare annual maintenance, call-outs, labour, parts and separate [inspection/testing and PTO-related work](#). A lower equipment price can be outweighed by more building work or narrower support cover.

How to Decide Without Overthinking



For a wheelchair user and companion, begin with the suitable Access and A5000 platform sizes and entry arrangements, then include PL2 if its Singapore supply and support can be established. The selected platform dimensions are too similar to justify a winner on width alone. If extra length is needed, compare the larger configurations instead of trying to make the smallest lift work.

For a tight existing opening, Cibes' separate shaft and cut-out figures give a useful starting point; Aritco's exterior dimensions need the matching opening drawing before deciding which fits. Where six stops are essential, the cited Access and A5000 specifications remain candidates while PL2 does not. Where holding a travel button is the obstacle, investigate a locally supported one-touch configuration or a cabin lift with automatic controls.

For any Singapore installation, [BCA requires registered installation and maintenance contractors and a valid PTO before use](#). A product's overseas certification does not replace that local process. Bring floor plans, the intended passenger and wheelchair dimensions, the floors to connect and any quotations to [DirectHome's home-lift service](#). Those details let the lift and the surrounding building work be discussed as one project.

More on home lifts

Article [Buying a House with a Home Lift? What to Check First](#)

[Article](#) [7 Things to Check Before Accepting a Home Lift Quote](#)

[Article](#) [No-Pit Home Lifts: Can You Install One Without Digging?](#)

[Related service](#) [Stairlifts](#)

Our service

Home Lifts for your home

Explore the service, then discuss what your home needs with our team.

[View service details ↗](#)

Still weighing your options?

Plan with the buying guide

Bring the choices, costs and questions together before deciding what to do next.

[Read the home lifts buying guide →](#)

[More home lifts articles →](#)

Ready to discuss your home? [WhatsApp our team](#) or [request a quote](#).